



Modular, compact, impactful - The GRUMIUM wall-mounted light can be installed on patios, building walls or in entrances to living spaces and, thanks to its optional covers in different designs, provides a flexible universal solution for many areas of application. The permanently installed and energy-saving LEDs delivering max. 10 watts are encompassed by a diffuser made of milky plastic and produce a pleasant warm white light with a luminous flux of 730 lm. The Grumium outdoor light with die-cast aluminium housing comes in an angular and rounded design and has degree of protection IP54.

Special features

- Can be customised using replaceable add-ons
- Warm white/cold white can be selected using a switch

Housing Material	Die-cast aluminium	IP Protection Class	IP 54
Housing Color	Grey	Life Time L70 / B50	30000 h
Material of Lens	Plastic	Switching Cycles	15000
Colour of Lens	White	Power Consumption	10 kWh/1000h
Protection Class	Protection class I/protective grounding	Energy Efficiency Class	F
Rated Input	10 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000/4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	450 lm		
Rated Angle of Reflection	138 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	3		
Light characteristics	Direct		
Light direction	Top, Below, Side		
Length	100 mm		
Width	70 mm		
Height	200 mm		
Base width	95 mm		
Base height	15 mm		
Base diameter	195 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-10 to 60 °C		