



Special features

- High IP protection
- High colour reproduction value
- Dim to warm

Housing Material	Aluminium
Housing Color	White
Protection Class	Protection class II/protective insulation
Rated Input	9 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Connection Cable Secondary	Yes
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

IP Protection Class	IP 65
Life Time L70 / B50	30000 h
Switching Cycles	100000
Power Consumption	9 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Colour Temperature	2000-2800 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	500 lm
Luminous Efficiency	55.6 lm/W
Rated Angle of Reflection	40 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	66 mm
Diameter	83 mm
Installation Depth	65 mm
Cut Out Diameter	68 mm
Product weight	312 g

Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C