



Modular, compact, impactful - the GRUMIUM wall-mounted light can be installed on patios, building walls or in entrances to living spaces and, due to its optional covers in different designs, provides a flexible universal solution for many areas of application. The permanently installed and energy-saving LEDs delivering max. 10 watts are encompassed by a diffuser made of milky plastic and produce a pleasant warm-white light with a luminous flux of 730 lm. The Grumium outdoor light with die-cast aluminium housing comes in an angular and rounded design and has a degree of protection IP54.

Special features

- Can be customised using interchangeable add-ons
- Warm white/cold white can be selected using a switch

Housing Material

Aluminium

Housing Color

Grey

Material of Lens

Plastic

Colour of Lens

White

Switching Cycles

15000

Power Consumption

10 kWh/1000h

EEI

F

Protection Class

Protection class I/protective grounding

Rated Input

10 W

Rated Input Voltage Frequency

220-240 V/AC 50 / 60 Hz

Power Supply Unit incl.

Yes

Connection Type

Clamp

Dimmable

No

Motion Detector

No

Light Source

LED, Light source not changeable

Color Temperature

3000/4000 K

Colour Consistency

6 SDCM

Colour Rendering Index (Ra)

80

Rated Luminous Flux

530 lm

Rated Angle of Reflection

138 Degree

Light Distribution

Symmetric

Distribution Characteristic 120°

NDLS

Length

100 mm

Width

70 mm

Height

200 mm

Base length

95 mm

Base width

15 mm

Base height

195 mm

Working Temperature

-20 to 40 °C

Storage Temperature

-10 to 60 °C

IP Protection Class

IP 54

Life Time L70 / B50

30000 h