






PEPA LINEAR LED track spotlight 48 V DC, DALI-2 dimmable
Article no. 43100083



Tender

LED track spotlight 48 V DC, DALI-2 dimmable, Rectangular. Luminaire length 300.0 mm, Luminaire width 22.5 mm, Hight 44.0 mm Weight 0.121 kg, with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, opal Luminous flux 750 lm, Power 1 x 9,6 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 90, Rated life time L70/B50 at 25 °C: 50.000 h, Housing material: Aluminium / Polycarbonate, Colour: black structure, Permissible ambient temperature (ta): 0 °C up to +35 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP20. For connection to an external driver, which is not included in the scope of delivery of the luminaire. DALI-2 dimmable.

Article data	
Article no.	43100083
GTIN	4255752520351
Series name	PEPA LINEAR
Short description	LED track spotlight 48 V DC, DALI-2 dimmable
Material	Aluminium / Polycarbonate
Colour	black structure
Type of surface	Matt
Shape	Rectangular
Length	300 mm
Width	22.5 mm
Hight	44 mm
Scope of delivery	inkl. DALI-2 Adapter
Weight	0.121 kg
D licence plate	No
Conformance	CE, UKCA


PEPA LINEAR LED track spotlight 48 V DC, DALI-2 dimmable

Article no. 43100083

Lighting technology	
Colour temperature	3.000 K
Light colour	white
Light output	Direct
Luminous flux	750 lm
System efficiency	78 lm/W
McAdam-Step	McAdam-Step 6
Colour rendering	CRI > 90
Reflector	Without
Beam angle	120°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	9.6 W
Voltage type	DC
AC nominal voltage min	48 V
AC nominal voltage max	48 V
Current	250 mA
Lamp	LED
Lamp holder	LED
Protection class	III
Degree of protection	IP20
Ambient temperature	0°C up to +35°C
Dimmable	Yes
Control	DALI-2
Minimum / maximum dimming range	1 - 100 %
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	50,000 h
Energy efficiency class	not required

Mounting technology	
Mounting method	Conductor rail mounting
Place of installation	Ceiling- /Wall-mounted
Adjustability	Not adjustable
Material cover	Plastic, opal
Suitable for through-wiring	No

Packing data	
Gross weight	0.164 kg
Length of packaging	300 mm
Packaging width	22 mm
Packaging height	44 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.