



Housing Material	Die-cast aluminium	IK Protection Class	IK10
Housing Color	Grey	Life Time L70 / B50	50000 h
Material of Lens	Polycarbonate - PC	Life Time L80 / B10	50000 h
Surface Structure of Lens	Clear	Switching Cycles	100000
Protection Class	Protection class I/protective grounding	Power Consumption	24 kWh/1000h
Rated Input	24 W	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class C.
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control technology	DALI 2 / DT6		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000 K		
Colour Consistency	4 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	1030 lm		
Rated Angle of Reflection	360 Degree		
Rated Angle of Reflection 2	180 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Side, Below		
Height	600 mm		
Diameter	180 mm		
Working Temperature	-30 to 45 °C		
Storage Temperature	-30 to 60 °C		
IP Protection Class	IP 65		