



Special features

- Including 2 m connecting cable with IP44 plug
- Including wireless remote control with approx. 20 m range.

Housing Material	Plastic
Housing Color	Black
Protection Class	Protection class I/protective grounding
Rated Input	62 W
Rated Input Voltage	100-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Power plug IP44
Primary Cable Length	2 m
Connection Type According to Standard	Typ Y
Dimmable	Yes
Control technology	RF 2,4 GHz
Motion Detector	No

IP Protection Class Plug	IP 44
Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption	62 kWh/1000h

Light Source	LED, Light source not changeable
Colour Consistency	6 SDCM
Rated Luminous Flux	2100 lm
Rated Angle of Reflection	120 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	200 mm
Width	98 mm
Height	253 mm

Working Temperature	-20 to 50 °C
Storage Temperature	-40 to 60 °C
IP Protection Class Lamp	IP 65