

## Han 10B-HMC-HTE-LC-for SL-M25



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 19 30 210 1441  |
| Specification      | Han 10B-HMC-HTE-LC-for SL-M25   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19302101441">https://b2b.harting.com/19302101441</a> |

### Identification

|                          |                      |
|--------------------------|----------------------|
| Category                 | Hoods/Housings       |
| Series of hoods/housings | Han <sup>®</sup> HMC |
| Type of hood/housing     | Hood                 |
| Type                     | Low construction     |

### Version

|                      |   |
|----------------------|---|
| Size                 | 10 B  |
| Version              | Top entry   |
| Cable entry          | 1x M25  |
| Locking type         | Single locking lever                              |
| Field of application | Special hoods and housings for high mating cycles |

### Technical characteristics

|   |                 |
|---|-----------------|
| Limiting temperature                    | -40 ... +125 °C |
| Mating cycles with other HMC components | ≥10,000         |
| Degree of protection acc. to IEC 60529  | IP65            |
| Type rating acc. to UL 50 / UL 50E      | 4<br>4X<br>12   |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast   |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 7037 (dust grey) |



Pushing Performance  
Since 1945

## Material properties

|                                      |                            |
|--------------------------------------|----------------------------|
| RoHS                                 | compliant                  |
| ELV status                           | compliant                  |
| China RoHS                           | e                          |
| REACH Annex XVII substances          | Not contained              |
| REACH ANNEX XIV substances           | Not contained              |
| REACH SVHC substances                | Not contained              |
| California Proposition 65 substances | Yes                        |
| California Proposition 65 substances | Nickel                     |
| Fire protection on railway vehicles  | EN 45545-2 (2020-08)       |
| Requirement set with Hazard Levels   | R1 (HL 1-3)<br>R7 (HL 1-3) |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 124.4 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140127616                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |