



The square JABBAH uses integrated COB LEDs in warm white, emitting its light asymmetrically at an angle of 75° onto walls in a cone of illumination - in a simple variant providing 915 lumens, as an UP AND DOWN version providing a total of 1,850 lumens. In addition, the two-sided JABBAH can be dimmed to 60 % luminous flux using a dip switch, if a more subtle light is desired.

Special features

- Modern design
- Dimmable to 60 % using DIP switch
- High luminous flux

| | | | |
|---|---|--------------------------------|---|
| Housing Material | Die-cast aluminium | Energy Efficiency Class | G |
| Housing Color | Grey | | |
| Protection Class | Protection class I/protective grounding | | |
| Rated Input | 25 W | | |
| Rated Input Voltage Frequency | 220-240 V/AC 50 / 60 Hz | | |
| Power Supply Unit incl. | Yes | | |
| Connection Type | Clamp | | |
| Dimmable | No | | |
| Motion Detector | No | | |
| Light Source | LED, Light source not changeable | | |
| Color Temperature | 3000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 80 | | |
| Rated Luminous Flux | 1850 lm | | |
| Rated Angle of Reflection | 75 Degree | | |
| Distribution Characteristic 120° | NDLS | | |
| Light Exit Surfaces | 2 | | |
| Light characteristics | Direct, Indirect | | |
| Light direction | Top, Below | | |
| Length | 150 mm | | |
| Width | 150 mm | | |
| Height | 150 mm | | |
| Working Temperature | -20 to 40 °C | | |
| Storage Temperature | -10 to 60 °C | | |
| IP Protection Class | IP 65 | | |
| Life Time L70 / B50 | 30000 h | | |
| Switching Cycles | 15000 | | |
| Power Consumption | 25 kWh/1000h | | |