



Special features

- Including connecting cable

| | |
|--------------------------------------|---|
| Housing Material | Stainless steel, Die-cast aluminium |
| Housing Color | Silver |
| Material of Lens | Glass |
| Protection Class | Protection class I/protective grounding |
| Rated Input | 4.1 W |
| Rated Input Voltage Frequency | 220-240 V/AC 50 / 60 Hz |
| Power Supply Unit incl. | Yes |
| Connection Cable Primary | Yes |
| Primary Connection | Connection box |
| Primary Cable Length | 0.5 m |
| Dimmable | No |
| Motion Detector | No |

| | |
|----------------------------|--------------|
| Working Temperature | -20 to 40 °C |
| Storage Temperature | -10 to 60 °C |
| IP Protection Class | IP 67 |
| Load Force max. | 20 kN |

| | |
|--------------------------------|-------------|
| Life Time L70 / B50 | 25000 h |
| Switching Cycles | 100000 |
| Power Consumption | 3 kWh/1000h |
| Energy Efficiency Class | G |

| | |
|---|----------------------------------|
| Light Source | LED, Light source not changeable |
| Color Temperature | 3000 K |
| Colour Consistency | 5 SDCM |
| Colour Rendering Index (Ra) | 80 |
| Rated Luminous Flux | 280 lm |
| Luminous Efficiency | 68.3 lm/W |
| Rated Angle of Reflection | 30 Degree |
| Light Distribution | Symmetric |
| Distribution Characteristic 120° | DLS |

| | |
|------------------------------|--------|
| Light Exit Surfaces | 1 |
| Light characteristics | Direct |
| Light direction | Top |

| | |
|---------------------------|--------|
| Height | 102 mm |
| Diameter | 116 mm |
| Installation Depth | 150 mm |
| Cut Out Diameter | 102 mm |
| Product weight | 1022 g |