



#### Product Features

Patch cord, Cat. 8.1/Class I, 3,0 m, shielded S/FTP, FRNC, LSOH, grey (similar RAL 7035)

- suitable for 40-Gigabit applications (bandwidth 2000 MHz)
- 2x RJ45-plugs
- S/FTP-version
- suitable for all common RJ45 data applications, respectively terminal devices
- fire protection classification according to EN 13501-6:Dca
- cladding material: LSOH, FRNC
- moulded bend protection
- bend radius without strain-relief > 20 mm
- cable structur:
- wire: Cu-braid, blank Ø 0,99 mm (AWG 26)
- isolation: Foam-Skin Polyethylen, Ø 0,98 mm
- according to following standards:
- DIN EN 50173-1
- ISO/IEC 11801
- suitable for PoE+ (IEEE802.3at)

#### Features

General	
shielded	Yes
Classification	Cat.8.1/Class I
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85444210
Country of manufacture	RO
GTIN (EAN)	4043921663981
Dimensions/Weights without packaging	
Cable length mm	3.000
Net weight piece kg	0,121
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes

Logistics Information	
Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,13
Packaging unit Width mm	270
Packaging unit Height mm	205
Packaging unit Depth mm	13
References	
Accessories	13900308, 13900310, 21200800
Similar article	21200010, 21200020, 21500030, 21500330, 21500430, 21500530, 21500630

