



The modern, towering ALHENA light with 360° light distribution not only lights up entrances, parking spaces, gardens and patios, it also stands apart as a design element owing to its surface-mounted design.

#### Special features

- Timeless design
- High luminous flux
- Homogeneous light distribution in all directions
- Powerful statement for expressive outdoor spaces
- Base dia.: 130 mm

<b>Housing Material</b>	Die-cast aluminium	<b>Power Consumption</b>	37 kWh/1000h
<b>Housing Color</b>	Black	<b>Energy Efficiency Class</b>	F
<b>Material of Lens</b>	Plastic		
<b>Protection Class</b>	Protection class I/protective grounding		
<b>Rated Input</b>	37 W		
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	3900 lm		
<b>Rated Angle of Reflection</b>	360 Degree		
<b>Distribution Characteristic 120°</b>	NDLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Side		
<b>Height</b>	1500 mm		
<b>Diameter</b>	110 mm		
<b>Base diameter</b>	110 mm		
<b>Working Temperature</b>	-20 to 50 °C		
<b>Storage Temperature</b>	-10 to 60 °C		
<b>IP Protection Class</b>	IP 65		
<b>Life Time L70 / B50</b>	26500 h		
<b>Switching Cycles</b>	50000		