
lightnet

Matric-A3

Surface mounted light-line - Direct light distribution





Article code: LA3LBE-840E-L1002-B

Illustrations may only be similar and serve as an orientation.

Matric-A3. LED. Wall or ceiling mounted light-line. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct only light distribution. Coloutemperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Lens Louvre: precision lenses with louvre. High glare limitation, compatible for office applications. UGR<=19. Reflector: Jet Black. Switchable. LxWxH (rectangular). L=1002mm. W= 55mm. H=75mm. Low-power current.

1830lm. 14W. 2,9kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.


lightnet


Matric-A3

Surface mounted light-line - Direct light distribution

Article code: LA3LBE-840E-L1002-B







Customer / Project:		
Note:		
Note.		

Productname Matric-A3 Lamp LED

Installation Type Surface mounted light-line

Surface finish Jet Black

Colour temperature 4000K
Colour Rendering Index (CRI) CRI>80
Optical system Lens Louvre
Reflector Colour Inside Reflector: Jet Black

Control Switchable
Length L/Diameter D (mm) L=1002mm
Width W (mm) W=55mm
Height H (mm) H=75mm
Current/Power Low-Power
Luminous Flux 1830lm
Power consumption 14W

Certification Prüfzeichen: ENEC

LED lifetime L90B10 (tq 25° C) = 50.000h

IP20

UGR UGR<=19
Photometric code 8 40 / 3 3 9
Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 2,9kg

Degree of protection

