



### Product Features

IP switching actuator/sensor, 8 x 16 A, 1 A/D-inputs, with network connection and integrated WIFI-Accesspoint, for DIN-rail mounting, light grey (similar RAL 7035)

- for DIN-rail mounting (144 mm)
- protection class IP20
- integrated power supply: 100 V-240V AC/50-60 Hz
- status indication of the switching outputs
- power consumption: 10 VA max.
- local handling for the switching outputs
- integrated clock timer
- temperature range -5°C to +45°C
- 8 switching outputs 16A/230V (cos phi = 1, detachable, screwless plug-in terminal up to 2,5mm<sup>2</sup>)
- 16 digital inputs for dry ccontacts
- switching outputs configurable for roller blinds (max.4)
- LED status indication of the switching outputs
- local handling for the switching outputs
- easy configuration via web browser
- 2 A/D inputs for sensors 0-10 V / 4-20 mA, configurable
- 16 digital inputs for dry ccontacts (detachable screw terminals)
- extensive logic functions for connections of the Input parameters
- network RJ44-port
- AND/OR links of the inputs
- link and activity LED für networkports
- integrated WLAN-Accesspoint (IEEE 802.3 b/g/n, 150 Mbit/s)
- with WLAN antenna and 2 m conduct
- service LED for WLAN
- time switching functions (annual time switch), with random generator
- USB front port (USB2.0) for adaption of a LTE/GSM-stick
- reset knob at the front panel
- password protection
- alarming functions by mail
- connection to amazon alexa or Google Home via additional hardware (AppModul)
- cross-platform handling via web browser
- SmartPhone control via App for free (iOs/Android)
- UDP protocoll assistance for all functions/parameters
- manual IP adress specification or dynamic specification via DHCP
- operator guidance at languages D/GB/NL/F
- light grey (similar RAL 7035)
- protection class according to EN60529 - IP20

- and much more
"- pre defined scenarios e.g. "all out/on", presens simulation and much more"
- 3 user defined scenarios configurable
- easy configuration via web browser
- network integration via LAN or WLAN
- network RJ45-port
- Link and activity LED für networkports
- integrated WLAN-Accesspoint (IEEE 802.3 b/g/n, 150 Mbit/s)
- with WLAN antenna and 2 m conduct
- service LED for WLAN
- USB front port (USB2.0) for adaption of A LTE/GSM-Stick
- reset knob at the front panel
- password protection
- connection to amazon alexa or Google home via additional hardware (AppModule)
- cross-platform handling via web browser
- SmartPhone control via App for free (iOs/Android)
- UDP protocoll assistance for all functions/parameters
- API interface for all functions/parameters
- function expansion with <R>-Control Plus Extension 4 via interface on the side
- manual IP adrees specification or dynamic specification via DHCP
- operator guidance at languages D/GB/NL/F

Features	
General	
Protection class IP	21
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921663936
Mounting types	
DIN-Rail	Yes
Dimensions/Weights without packaging	
Length mm	144
Width mm	90
Height mm	59
Net weight piece kg	0,448
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,626
Packaging unit Width mm	185
Packaging unit Height mm	145
Packaging unit Depth mm	95
References	
Accessories	700802612, 700802613, 700802614, 700802616
Similar article	700802610, 700802615

