

# D SUB HD MA CRIMP SHELL 26P



Part number	09 56 200 5601
Specification	D SUB HD MA CRIMP SHELL 26P
HARTING eCatalogue	https://b2b.harting.com/09562005601

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	D-Sub
Identification	High Density
Element	Connector

#### Version

Termination method	Crimp termination
Gender	Male
Size	D-Sub 2
Number of contacts	26
Locking type	Fixing flange with feed through hole Ø 3.1 mm

#### Technical characteristics

Conductor cross-section	0.14 0.25 mm <sup>2</sup>
Conductor cross-section	AWG 26 AWG 24
Conductor cross-section	AWG 20 AWG 24
Wire outer diameter	≤1.38 mm
Clearance distance	≥1 mm
Clearance distance	21111111
Creepage distance	≥1 mm
	2
Insulation resistance	$> 5 \times 10^9 \Omega$
Limiting temperature	-40 +85 °C
Eliming temperature	
Test voltage U <sub>r.m.s.</sub>	1 kV
Isolation group	IIIa (175 ≤ CTI < 400)



#### Technical characteristics

Hot plugging No

## Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled (PBTP) Shell: steel, nickel plated
Colour (insert)	Black
Material (contacts)	Copper alloy
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide Lead
Requirement set with Hazard Levels	R26

# Specifications and approvals

Specifications	DIN 41652
UL / CSA	UL 1977 ECBT2.E102079

### Commercial data

Packaging size	100
Net weight	5.14 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140071445
eCl@ss	27440214 D-Sub coupler