

| | | | | | | | | |
|---|---|-----------------------------------|----------------------------|-----------|-------------|------|---------------------------|-------------------------|
| a) Lieferant supplier's name | | Maico Elektroapparate-Fabrik GmbH | | | | | | |
| b) Modellkennung (Code) supplier model identifier (code) | | WS 120 Trio LR (0095.0657) | | | | | | |
| c) Spezifischer Energieverbrauch specific energy consumption SEC class - climate zone „average“ | SEC | kalt / cold | mittel / average | | warm / warm | | kWh / (m ² ·a) | |
| | | -78,74 | -36,82 | | -12,81 | | | |
| | | A | | | | | | |
| d) Typ typology | RVU | x | BVU | | x | | | |
| | NRVU | - | | UVU | | - | | |
| e) Art des eingebauten / einzubauenden Antriebes type of drive installed / intended to be installed | multi-speed | - | | installed | | X | | |
| | VSD | x | intended to be instal. | | - | | | |
| f) Art des Wärmerückgewinnungssystems (WRG) type of heat recovery system | rekuperativ / recuperative | x | regenerativ / regenerative | | - | | keines / none | |
| | | | | | | - | | |
| g) Temperaturänderungsgrad der WRG thermal efficiency of heat recovery | η_t | 80,9 | | | | % | | |
| h) Höchster Luftvolumenstrom maximum flow rate | | | | | 120 | | m ³ /h | |
| i) Elektrische Eingangsleistung Ventilatorantrieb electric power input of the fan drive | | | | | 24,5 | | W | |
| j) Schalleistungspegel sound power level | $L_{WA..}$ | | | | | 39,9 | | dB[A] |
| k) Bezugs-Luftvolumenstrom reference flow rate | | | | | 0,02333 | | m ³ /s | |
| l) Bezugsdruckdifferenz reference pressure difference | | | | | 50 | | Pa | |
| m) Spezifische Eingangsleistung specific power input | SPI | | | | | 0,29 | | W/(m ³ /h) |
| n) Steuerungsfaktor und Steuerungstypologie control factor and control typology | CTRL | MISC | | X-Value | | - | | |
| | 0,85 | 1,1 | | 2 | | | | |
| o) Innere Höchstleckluft rate / Äußere Höchstleckluft rate max. internal leakage rate / max. external leakage rate | innere / internal | 1,1 | äußere / external | | 1,7 | | % | |
| p) Mischrate mixing rate | | | | | - | | % | |
| q) Lage und Beschreibung optische Filterwarnanzeige position and description of visual filter warning | LED - replace the filter continuously to preserve the device properties | | | | | | | |
| r) Anweisungen für Anbringung regelbarer AUL- / ABL-Gitter instructions to install regulated supply/exhaust grilles | - | | | | | | | |
| s) Internetadresse für Anweisungen zur Zerlegung/Demontage internet address for disassembly instructions | www.maico-ventilatoren.com | | | | | | | |
| t) Druckschwankungsempfindlichkeit Luftstrom airflow sensitivity to pressure variations at -20 Pa / +20 Pa | | | | | - | | % | |
| u) Luftdichtheit zwischen innen und außen indoor / outdoor air tightness | | | | | - | | m ³ /h | |
| v) Jährlicher Stromverbrauch annual electricity consumption | AEC | | | | | 3,1 | | kWh/(m ² ·a) |
| w) Jährliche Einsparung an Heizenergie annual heating saved | AHS | kalt/cold | mittel / average | | warm / warm | | kWh/(m ² ·a) | |
| | | 85,7 | 43,8 | | 19,8 | | | |