## lightnet

## Basic-P5

Pendant luminaire - Direct/indirect light distribution





Article code: BP5ABL-830H-D800-P

Illustrations may only be similar and serve as an orientation.

Basic-P5. LED. Pendant luminaire. Luminaire body with 38mm visible overall height and minimalist edge of only 5mm. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Dimmable DALI. DxH (round). D=800mm. H=38mm. Rod suspension with ceiling rose (Set).

Pendant length on request. Ceiling rose: Matching luminaire`s surface colour. High-power current. 9752lm. 81W. 9,5kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

## lightnet


## Basic-P5

Pendant luminaire - Direct/indirect light distribution

Article code: BP5ABL-830H-D800-P



Customer	/ Project:		
Note:			



min. 200

max. on request

38

2/2

Basic-P5 Productname LED Lamp

Installation Type Pendant luminaire

Surface finish Jet Black

Light characteristics Direct/indirect light distribution

3000K Colour temperature Colour Rendering Index (CRI) CRI>80

Optical system Microprismatic screen Control Dimmable (DALI) Length L/Diameter D (mm) D=800mm H=38mm Height H (mm) Current/Power High-Power Luminous Flux 9752lm 81W Power consumption

Suspension Rod susp. (Set)

Ceiling rose colour Ceiling rose: Matching luminaire`s

surface colour

Pendant length (mm) Pendant length on request

Degree of protection IP40

Certification Prüfzeichen: ENEC

LED lifetime L80B10 (tq  $25^{\circ}$ C) = 50.000h

**UGR** UGR<=19 Photometric code 8 30 / 3 3 9 Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 9,5kg



































