



Versatile and functional - The Mensae LED outside wall and ceiling light boasts an impressive flat design and can be used both indoors and outdoors with its movement sensor including daylight sensor. The white cover atop the dark grey aluminium die-cast frame houses 96 warm white LEDs with 18 watts and 3,000 K.

Housing Material	Die-cast aluminium	Life Time L70 / B50	30000 h
Housing Color	Grey	Switching Cycles	100000
Material of Lens	Plastic	Power Consumption	22 kWh/1000h
		Energy Efficiency Class	G
Protection Class	Protection class I/protective grounding		
Rated Input	20 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	1240 lm		
Rated Angle of Reflection	115 Degree		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top, Below, Side		
Length	300 mm		
Width	300 mm		
Height	48 mm		
Base height	28 mm		
Base diameter	170 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 54		

