



Small, fine, elegant and discreet - The ACAMAR is a light manufactured from high-quality aluminium. The colour reproduction value is over 90, which means high colour authenticity. The design is chic and interesting thanks to the rounding on one side. You can mount the light with the rounding upwards or downwards, depending on your preference. The white paint inside accentuates the warm white light and ensures pleasant scattering upwards and downwards. The outside is highly polished for an incredible shine.

#### Special features

- Very high colour reproduction value
- High light emission angle

<b>Housing Material</b>	Die-cast aluminium	<b>Life Time L70 / B50</b>	30000 h
<b>Housing Color</b>	Black	<b>Switching Cycles</b>	100000
<b>Protection Class</b>	Protection class I/protective grounding	<b>Power Consumption</b>	7 kWh/1000h
<b>Rated Input</b>	6.9 W	<b>Energy Efficiency Class</b>	G
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	90		
<b>Rated Luminous Flux</b>	250 lm		
<b>Rated Angle of Reflection</b>	104 Degree		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Top, Below		
<b>Length</b>	170 mm		
<b>Width</b>	100 mm		
<b>Height</b>	80 mm		
<b>Base length</b>	120 mm		
<b>Base width</b>	60 mm		
<b>Base height</b>	33 mm		
<b>Working Temperature</b>	-5 to 40 °C		
<b>Storage Temperature</b>	-10 to 60 °C		
<b>IP Protection Class</b>	IP 20		