



The elegant APODIS wall light captivates with its high-quality aluminium housing with compact base and a fine two-colour coating in black and gold. The Apodis emits powerful warm white light both upwards and downwards via the double light output. The light can be dimmed flexibly using leading/trailing phase angles.

Special features

- Exceptional design
- Dimmable
- High colour reproduction value

Housing Material	Aluminium
Housing Color	Gold
Protection Class	Protection class I/protective grounding
Rated Input	10.8 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

IP Protection Class	IP 20
Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption	11 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	350 lm
Rated Angle of Reflection	40 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	2
Light characteristics	Direct
Light direction	Below, Top

Length	76 mm
Width	61 mm
Height	500 mm
Base length	60 mm
Base width	18 mm
Base height	100 mm

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C