



Special features

- Including connecting cable

Housing Material	Stainless steel
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	16.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	WEIPU plug 4-pole
Secondary Cable Length	0.5 m
Dimmable	Yes
Control technology	Dimmable via optional controller
Motion Detector	No

Cut Out Width	58 mm
Product weight	1127 g
Working Temperature	-20 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	20 kN
Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption	11 kWh/1000h

Light Source	LED, Light source not changeable
Colour Consistency	6 SDCM
Rated Luminous Flux	400 lm
Luminous Efficiency	24.2 lm/W
Rated Angle of Reflection	50 Degree
Rated Angle of Reflection 2	35 Degree
Light Distribution	Asymmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	328 mm
Width	63 mm
Height	65 mm
Installation Depth	90 mm
Cut Out Length	313 mm