



Special features

- Light directed downwards, dimmed by the slatted insert

Housing Material	Die-cast aluminium	Life Time L70 / B50	30000 h
Housing Color	Grey	Switching Cycles	100000
Material of Lens	Glass	Power Consumption	16 kWh/1000h
		Energy Efficiency Class	G
Protection Class	Protection class I/protective grounding		
Rated Input	15.9 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Connection box		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	510 lm		
Rated Angle of Reflection	360 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Side		
Height	1000 mm		
Diameter	120 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 54		
IK Protection Class	IK05		