

Phase sequence indicator - test plug



| Product description | |
|---------------------------|--------------------------|
| BALS-Prd.-Nr | 2221 |
| EAN | 4024941022217 |
| Product category | Phase sequence indicator |
| Current | 32A |
| Number of poles | 5p |
| Poles | 3p+N+PE |
| Position of earth contact | 7 h |
| Voltage | 277/480 up to 288/500V |
| Frequency | 50 and 60Hz |

| Product description | |
|---|-------|
| Protection degree | IP44 |
| Indication three phases | yes |
| Motor rotation direction tester | FALSE |
| Contact less detection of the sense of rotation | yes |
| Height | 143mm |
| Width | 73mm |
| Depth | 73mm |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.255 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941022217 |
| Length | 73 mm |
| Width | 73 mm |
| Height | 143 mm |
| Weight | 0.256 kg |
| Volume | 762.047 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941834490 |

| Logistics data | |
|----------------|-----------|
| Length | 245 mm |
| Width | 177 mm |
| Height | 185 mm |
| Weight | 2.683 kg |
| Volume | 7,140 ccm |