

**Special features**

- High colour reproduction value
- Small installation diameter

Housing Material	Aluminium
Housing Color	Silver
Housing Surface	Shiny
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	1 W
Rated Input Voltage	3.1-3.9 V/DC
Rated Current	350 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Dimmable	No
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	40 lm
Luminous Efficiency	40 lm/W
Rated Angle of Reflection	50 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	25 mm
Diameter	30 mm
Installation Depth	30 mm
Cut Out Diameter	18 mm
Product weight	52 g

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 44

Life Time L70 / B50	30000 h
Switching Cycles	100000
Power Consumption	1 kWh/1000h