



It takes a lot to catch the Altas series off guard. Thanks to IP54 and impact strength class IK10, these slender outdoor lights are impressive all rounders both in a commercial and private setting. The Altas lights offer additional flexibility with their integrated movement sensor [programmable using remote control] and the adjustable light colour for different lighting scenarios.

Special features

- Light colour adjustable in 3 stages
- High impact resistance
- Splash water protected

Housing Material	Plastic
Housing Color	White
Protection Class	Protection class II/protective insulation
Rated Input	18 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	High frequency
Detection Distance	1-12 m
Angle of Detection	150 Degree
Light Source	LED, Light source not changeable
Color Temperature	3000/4000/6000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	85
Rated Luminous Flux	1870 lm
Rated Angle of Reflection	120 Degree
Distribution Characteristic 120°	NDLS
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Height	49 mm
Diameter	280 mm
Working Temperature	-40 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 54
IK Protection Class	IK10

Life Time L70 / B50	50000 h
Switching Cycles	75000
Power Consumption	18 kWh/1000h
Energy Efficiency Class	D