



This pendant lamp is distinct for its transparent luminous element. The surface is almost completely see-through when switched off. When the light is switched on, the pane distributes the light almost entirely without glare. This pendant lamp is fully office-compatible with a glare value [UGR] of under 19. Bright, efficient and with a sophisticated design, this light stands out in any type of office environment.

Special features

- Very low glare value
- Transparent luminous element
- Max. suspended mounting 1,500 mm

Housing Material	Aluminium
Housing Color	Black
Material of Lens	PMMA
Protection Class	Protection class I/protective grounding
Rated Input	50 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Light Source	LED, Light source changeable TC
Color Temperature	3000/3500/4000 K
Colour Consistency	5 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	6000/6100/6100 lm
Rated Angle of Reflection	140 Degree
Rated Angle of Reflection 2	150 Degree
UGR	22
Light Distribution	Symmetric

Light Exit Surfaces	1
Light characteristics	Direct, Indirect
Light direction	Top, Below

Height	12 mm
Diameter	633 mm
Base height	43 mm
Base diameter	215 mm
Pendulum Length max.	1800 mm

Working Temperature	-10 to 55 °C
Storage Temperature	-20 to 60 °C
IP Protection Class	IP 40
IK Protection Class	IK04
Life Time L70 / B50	75000 h
Life Time L80 / B10	50000 h
Life Time L80 / B50	60000 h
Power Consumption	50 kWh/1000h
Energy Efficiency Class Lightsources	This product contains a light source of energy efficiency class C.

