



Especially when it comes to lighting house entrances, patios or other access paths, spotlights specially designed for outdoors are the way to go. The protection classes required for such are part and parcel and different colours and shapes are options. Universal use and not to be overlooked as a security product.

Housing Material	Plastic	IP Protection Class	IP 65
Housing Color	Grey	Life Time L70 / B50	30000 h
Material of Lens	Plastic	Switching Cycles	50000
Colour of Lens	White	Power Consumption	10 kWh/1000h
Protection Class	Protection class II/protective insulation	Energy Efficiency Class	G
Rated Input	10 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	680 lm		
Rated Angle of Reflection	115 Degree		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	220 mm		
Width	220 mm		
Height	56 mm		
Base length	190 mm		
Base width	190 mm		
Base height	10 mm		
Working Temperature	-20 to 50 °C		
Storage Temperature	-20 to 50 °C		