



When it comes to illuminating signs, façades, billboards or images, display lights are the perfect choice. They are easy to install, exceptionally efficient and suit almost any environment thanks to their timeless design. With corresponding IP protection, they can also be used outdoors, purposefully providing an additional lighting source in such environments.

Special features

- Base H x dia.: 40 x 95 mm
- Rotatable and swivelling lamp head

Housing Material	Die-cast aluminium
Housing Color	Black
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	15 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No
Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1150 lm
Rated Angle of Reflection	100 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS
Swivel Angle	90 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Length	526 mm
Width	144 mm
Base length	95 mm
Base height	40 mm
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C

IP Protection Class	IP 65
Life Time L70 / B50	50000 h
Switching Cycles	15000
Power Consumption	15 kWh/1000h
Energy Efficiency Class	F

