

Wall mounting socket outlet, fused - housing dimensions 260x160 with mounting rail



Product description	
BALS-Prd.-Nr	15130
EAN	4024941151306
product category (PG)	GT wall mounting socket outlet, fused
current (A)	32A
number of poles (P99)	5p
number of poles (P)	3p+N+PE
position of earth contact (H)	6 h
voltage (V)	200/346 up to 240/415V

Product description	
frequency (HZ)	50 and 60Hz
protection degree (SA)	IP44
colour code 1 (KF1)	red RAL 3000
Colour of appliance	Operating window smoky topaz, Hinged lid red RAL 3000, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035
connection design (AT)	with screw terminal
maximum conductor size (LQ)	10,0 qmm
cable entry (KE)	top entry M40 bottom entry M40/M32
Height	287mm
Width	160mm
Depth	165mm
dimension of enclosure (GG)	260x160 mm (HxW)
material of enclosure (GM)	Polycarbonate
contact	The contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical properties	
	The cable entry is one at top and two at bottom open
	With mounting rail, With mounting rail for 7 modules, vertical, Protective cover for fuses with stamping

Logistics data	
Weight/pcs	1.555 kg / Piece

Logistics data	
Packaging	Carton
Content amount	1 ST
EAN	4024941151306
Length	326 mm
Width	217 mm
Height	210 mm
Weight	1.771 kg
Volume	13,588.4 ccm



14 MB 14