lightnet

Basic-P5

Pendant luminaire - Direct/indirect light distribution





Article code: BP5OBE-840M-D800-P

Illustrations may only be similar and serve as an orientation.

Basic-P5. LED. Pendant luminaire. Luminaire body with 38mm visible overall height and minimalist edge of only 5mm. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct/indirect light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Switchable. DxH (round). D= 800mm. H=38mm. Rod suspension with ceiling rose (Set). Pendant

length on request. Ceiling rose: Matching luminaire`s surface colour. Medium-power current. 7750lm. 60W. 9,5kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

lightnet


Basic-P5

Pendant luminaire - Direct/indirect light distribution

Article code: BP5OBE-840M-D800-P







Basic-P5 Productname LED Lamp

Installation Type Pendant luminaire

Surface finish Jet Black

Light characteristics Direct/indirect light distribution

4000K Colour temperature Colour Rendering Index (CRI) CRI>80 Optical system Opal diffuser Control Switchable Length L/Diameter D (mm) D=800mm Height H (mm) H=38mm Current/Power Medium-Power Luminous Flux 7750lm

60W Power consumption

Suspension Rod susp. (Set)

Ceiling rose: Matching luminaire`s Ceiling rose colour

surface colour

Pendant length (mm) Pendant length on request

Degree of protection IP40

Certification Prüfzeichen: ENEC

LED lifetime L85B10 (tq 25° C) = 50.000h

Photometric code 8 40 / 3 3 9 Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 9,5kg























