



SLIM series lights include single-luminaire and triple-luminaire pendant lamps and matching pendant lamps for the DEKO-LIGHT current track system. The light body in die-cast aluminium is always the same size (300 x 39 mm). Several SLIM models therefore can also be combined with each other in larger spaces. The pendant lamps for ceiling installation with max. 180 cm suspended mounting are available in a one or three-luminaire variant; three-luminaire variant both with long or round base depending on the arrangement of the lights.

Special features

- Die-cast aluminium
- Fabric cable
- Particularly glare-free thanks to low UGR value
- Suspended mounting up to 1800 mm

Housing Material	Aluminium	Pendulum Length max.	1800 mm
Housing Color	Black	Working Temperature	-20 to 45 °C
Material of Lens	PMMA	Storage Temperature	-20 to 65 °C
Colour of Lens	Transparent	IP Protection Class	IP 20
Surface Structure of Lens	Structured	Life Time L70 / B50	50000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	100000
Rated Input	15 W	Power Consumption	15 kWh/1000h
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	2700 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	1500 lm		
Rated Angle of Reflection	24 Degree		
UGR	19		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	3		
Light characteristics	Direct		
Light direction	Below		
Height	300 mm		
Diameter	39 mm		
Base height	25 mm		
Base diameter	240 mm		