



HAR-FLEX 80 POLE FEMALE CONNECTOR

HAR-FLEX 80 POLE FEMALE CONNECTOR

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
79	AWG 30	79
80	AWG 30	80

HARTING P/N	Cable length (L)
33152430100149	100±3
33152430200149	200±5
33152430300149	300±5
33152430500149	500±5

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE  
HARTING P/N

	All rights reserved Department HCS - CN	Created by ZHENGL Zheng	Inspected by QINL Qin	Standardisation QINL Qin	Date 2019-06-05	State Final Release	All Dimensions in mm Original Size DIN A3	Scale 1.5:1	Free size tol. \	Ref. \
							HARTING Customised Solutions D-32339 Espelkamp	Title Har-Flex 80 Pole,Dul-end,W/O SR,L=XX MM	Type TB	Number 33150032