

Date: 23.11.2021



Wall mounting socket outlet - housing dimensions 90x90



Product description				
BALS-PrdNr	110711			
EAN	4024941222297			
Product category	Wall mounting socket outlet			
Current	16A			
Number of poles	5p			
Arangement of phases	3p+N+PE			
Position of earth contact	6 h			
Voltage	200/346 - 240/415V~			
Frequency	50/60Hz			

CEE-Norm UK Ltd. Unit 2, Highbridge Court, Stafford Park 1, TF3 3BD Telford UK phone: +44 1952 212700 / fax: +44 1952 212711 / email: sales@ceenorm.co.uk



Date: 23.11.2021

Bals

Product description				
Protection degree	IP44			
Colour code	red RAL 3000			
Colour of appliance	white similar to RAL 9016			
Connection design	with screw terminal			
Maximum conductor size	4,0 qmm			
Cable entry	Anti-kink sleeve			
Height	90mm			
Width	90mm			
Depth	95mm			
Dimension of enclosure	90x90 mm			
Material of enclosure	ABS + Polycarbonate			
Contacts	the contacts are brass nickel plated			


Additional technical properties	
	Architecture programme TH, hinged lid with labelling field (optional: key lock), The cable entry is one at top open and one at bottom and one rear side closed

Logistics data		
Weight/pcs	0.318 kg / Piece	
Packaging	Bag	
Content amount	1 ST	
EAN	4024941222297	

CEE-Norm UK Ltd. Unit 2, Highbridge Court, Stafford Park 1, TF3 3BD Telford UK phone: +44 1952 212700 / fax: +44 1952 212711 / email: sales@ceenorm.co.uk

Bas www.bals.com Date: 23.11.2021

Logistics data				
Length	95 mm			
Width	90 mm			
Height	90 mm			
Weight	0.319 kg			
Packaging	Carton			
Content amount	6 ST			
EAN	4024941222594			
Length	370 mm			
Width	218 mm			
Height	125 mm			
Weight	2.081 kg			
Volume	9,329.4 ccm			



Ampere Poles	16 3	16 4	16 5	32 5	Schutzk. Domestic	
а	90,0	90,0	90,0	90,0	90,0	
b	90,0	90,0	90,0	90,0	90,0	
С	73,0	73,0	73,0	73,0	73,0	
d	73,0	73,0	73,0	73,0	73,0	
е	47,0	47,0	47,0	47,0	47,0	
f	48,0	48,0	48,0	48,0	48,0	
g	25,0	25,0	25,0	25,0	25,0	
Cond. mm² min.	1,0	1,0	1,0	2,5	1,0	
Cond. mm² max.	4,0	4,0	4,0	10	2,5	

4MB463



