

## Product Highlights

### High-Speed Networking

Gigabit ports allow you to connect up to eight devices for fast file transfers and smooth media streaming

### Save Energy Automatically

Energy Efficient Ethernet compliance reduces energy consumption without sacrificing performance while cutting down on your power bill

### Eco-Friendly and Economical

Economical yet innovative design runs cool and quiet, making for an unobtrusive addition to the workplace



## GO-SW-8G

# 8-Port Gigabit Easy Desktop Switch

## Features

### Connectivity

- Eight Gigabit Ethernet LAN ports for high-speed wired connections
- Cable Diagnostics Function notifies users of cable conditions through product LEDs

### Green Ethernet

- Reduces power to a port when no link is detected
- Adjust power to a port by detecting the length of the connected Ethernet cable

The dlinkgo GO-SW-8G 8-Port Gigabit Easy Desktop Switch is part of D-Link's series of small office and home devices that make use of D-Link's Green Technology, providing energy savings, reduced heat, and a longer product life without sacrificing performance or functionality. It provides eight Gigabit ports for easy expansion of your network and a quick way to upgrade your network to Gigabit connectivity. An energy-efficient power adapter (Energy Star Level V qualified), minimised use of harmful substances (RoHS compliant), and recyclable packaging make this switch truly environmentally friendly.

## Fast and Reliable Networking

The dlinkgo GO-SW-8G 8-Port Gigabit Easy Desktop Switch creates a blazing fast network for your office, as its Gigabit Ethernet ports provide high-speed wired connections for up to eight PCs or other devices. The GO-SW-8G also supports QoS, allowing you to prioritise network traffic so that time-sensitive data is delivered efficiently, even during bursts of high data traffic. It's stylish, easy-to-use, and comes IPv6-ready for a reliable network today and tomorrow.

## Conserve Energy

The 8-Port Gigabit Easy Desktop Switch helps you conserve energy automatically through several methods. It automatically powers down ports that have no link, allowing the switch to save a substantial amount of power by cutting power usage for unused ports. It also adjusts the amount of power supplied to a port according to the length of the connected Ethernet cable.

# GO-SW-8G 8-Port Gigabit Easy Desktop Switch

Technical Specifications		
General		
Device Interfaces	• Eight 10/100/1000BASE-T Gigabit LAN ports	
Functionality		
Advanced Features	<ul style="list-style-type: none"> <li>• Green Ethernet</li> <li>• 10 Gbps switching fabric</li> <li>• Auto MDI/MDIX crossover for all ports</li> <li>• Secure store-and-forward switching scheme</li> </ul>	<ul style="list-style-type: none"> <li>• Full/half-duplex for Ethernet/Fast Ethernet speeds</li> <li>• IEEE 802.3x Flow Control</li> <li>• Supports 9,216 Byte Jumbo Frames</li> <li>• Supports IEEE 802.1p QoS (4 Queues, Strict Mode)</li> <li>• Supports Cable Diagnostics Function</li> </ul>
Standards	<ul style="list-style-type: none"> <li>• IEEE 802.3 10BASE-T Ethernet (twisted-pair copper)</li> <li>• IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper)</li> <li>• IEEE 802.3ab 1000BASE-T Gigabit Ethernet (twisted-pair copper)</li> </ul>	<ul style="list-style-type: none"> <li>• ANSI/IEEE 802.3 NWay auto-negotiation</li> <li>• IEEE 802.3x Flow Control</li> <li>• IEEE 802.3az Energy-Efficient Ethernet (EEE)</li> </ul>
Protocol	• CSMA/CD	
Data Transfer Rates	<ul style="list-style-type: none"> <li>• Ethernet: <ul style="list-style-type: none"> <li>• 10 Mbps (half duplex)</li> <li>• 20 Mbps (full duplex)</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>• Fast Ethernet: <ul style="list-style-type: none"> <li>• 100 Mbps (half duplex)</li> <li>• 200 Mbps (full duplex)</li> </ul> </li> <li>• Gigabit Ethernet: <ul style="list-style-type: none"> <li>• 2000 Mbps (full duplex)</li> </ul> </li> </ul>
Transmission Method	• Store-and-forward	
MAC Address Table	• 8 K	
MAC Address Learning	• Automatic Update	
Packet Filtering/Forwarding Rates	<ul style="list-style-type: none"> <li>• Ethernet: 14,880 pps per port</li> <li>• Fast Ethernet: 148,800 pps per port</li> </ul>	• Gigabit Ethernet: 1,488,000 pps per port
RAM Buffer	• 128 KB per device	
Physical		
LED Indicators	• Per port: Link/Activity	• Per device: Power
Media Interface Exchange	• Auto MDI/MDIX adjustment for all ports	
Dimensions	• 130 x 79 x 22 mm	
Weight	• 130 grams	
Power	• 5 V/1 A Power Adapter	
Power Consumption	• Maximum: 2.55W	• Standby: 0.4W
Temperature	• Operating: 0 to 40 °C (32 to 104 °F)	• Storage: -10 to 70 °C (14 to 158 °F)
Humidity	• Operating: 10% to 90% non-condensing	• Storage: 5% to 90% non-condensing
MTBF	• 1,046,811 hours	
Certifications	• CE class B, CB, LVD	



For more information: [www.dlink.com](http://www.dlink.com)

**D-Link European Headquarters.** D-Link (Europe) Ltd., First Floor, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2020 D-Link Corporation. All rights reserved. E&OE.

Updated February 2020

**dlinkgo**  
by **D-Link**