



Housing Material	Copper	Length	5000 mm
Housing Color	White	Width	7.5 mm
Material of Lens	Silicone	Height	3 mm
Protection Class	Protection class III/safety extra-low voltage	Product weight	178 g
Operating Mode	Constant voltage	Working Temperature	-10 to 60 °C
Rated Input 1m	12.5 W	Storage Temperature	-15 to 50 °C
Rated Input Voltage	24 V/DC	IP Protection Class	IP 65
Power Supply Unit incl.	No	Type of IP Protection	Silicone hose
Connection Cable Primary	Yes	Life Time L70 / B50	30000 h
Primary Connection	With free strand / conductor ends	Switching Cycles	100000
Primary Cable Length	1 m	Power Consumption	13 kWh/1000h
Connection Cable Secondary	Yes	Energy Efficiency Class	G
Secondary Connection	Open cables		
Secondary Cable Length	1 m		
Dimmable	Yes		
Control technology	Dimmable via optional controller		
Light Source	LED, Light source not changeable		
Lightcolor	Warm white/cold white		
Colour Temperature	3000-6500 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Angle of Reflection	120 Degree		
Distribution Characteristic 120°	DLS		
Luminous Flux 1m	1070 lm		
Luminous Efficiency 1m	85.6 lm/W		
LED/Meter	196		
Bending Radius min.	50 mm		
Total Length to be Operated max.	5 m		
Segment Length	71.4 mm		
Segment LED Quantity	14		
LED Distance	10.2 mm		