



Product Features

"splice box, extensible, 19"/1U, 12xLC-D, OS2, blau"

- sheet steel housing, powder coated
- labelled ports
- with slide-in unit, max. pullout depth ca. 20 cm
- can be tilted downwards when opened
- can be locked with knurled screws
- the box can be offset by 40 mm towards the rear
- splice cassette for holding 12 or 24 pigtails
- can be equipped with max. 4 splice cassettes (fixed)
- inserted crimp splice holder
- ready to splice with exposed and inserted pigtails incl. 12 x LC-D - ceramic couplings
- LC-fibre pigtails E9/125 Åm, 2 m, SM PC, grade B
- with test protocol for all fibres incl. serial number
- mounted blind stops by less than 24 ports
- 4 x PG16 - cable glands in the back (each 2 x right/left)
- 1 x PG16 - cable gland in scope of delivery
- light grey (similar RAL 7035)

Features

General	
Surface	steel sheet, powder-coated
Classification	OS2
Protection class IP	20
Halogen Free	Yes
Country of manufacture	DE
GTIN (EAN)	4043921664308
Mounting types	
(19-inch)-installation, 1 rack unit	Yes
Dimensions/Weights without packaging	
Length mm	482
Width mm	231
Height mm	44
Net weight piece kg	2,506
Certifications	
RoHS conform	Yes

Spleissbox 12xLC-D OS2 blau

Article no.: 228030312

Color: lightgrey (ähnlich RAL-Nr. 7035)

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	2,736
Packaging unit Width mm	500
Packaging unit Height mm	50
Packaging unit Depth mm	325
References	
Accessories	228040002, 228040102, 228040202, 228040302, 228040402, 228060000, 228060100, 228060200, 228060300, 228060400, 228070000, 228070100, 228070200, 228070312
Similar article	228030012, 228030112, 228030212, 228030306, 228030324, 228030412, 228030812, 228031212