



Special features

- Ideal for homogeneous basic lighting
- Slim design
- Can be rotated and swivelled
- High luminous flux

Housing Material	Aluminium
Housing Color	White
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Rated Input	20 W
Rated Input Voltage Frequency	110-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Adapter
Dimmable	No
Motion Detector	No

IP Protection Class	IP 20
Life Time L70 / B50	50000
Switching Cycles	30000
Power Consumption	20 kWh/1000h
Energy Efficiency Class	F

Light Source	LED, Light source not changeable
Lightcolor	Warm white (WW)
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	2000 lm
Luminous Efficiency	100 lm/W
Rated Angle of Reflection	110 Degree
UGR	28
Distribution Characteristic 120°	DLS

Swivel Angle	90 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	300 mm
Width	110 mm
Height	8.5 mm

Working Temperature	-10 to 35 °C
Storage Temperature	-20 to 45 °C