

IS-1 CS LED Gangdach
IS-1 CS LED aisle roof
iQdata Cooling



Abbildung ähnlich / picture similar

Technische Daten Technical data		
Material: <i>Material:</i>	Korpus LED Panel: Stahlblech Rahmen LED Panel: Aluminium Abdeckung LED Panel: Acrylglas Auflageleisten: Aluminium (T-Profil, 50x50x2 mm), eloxiert	Body LED panel: Sheet steel Frame LED panel: Aluminum Cover LED panel: Acrylic glass Support profiles: Aluminum (T-profile, 50x50x2 mm), anodized
Technische Daten LED Panel: <i>Technical data LED panel:</i>	Lebensdauer: 40.000 h nach IEC/PAS 62717 Schutzklasse: II schutzisoliert Schutzart: IP20 Nennleistung: 50 W Lichtausbeute: 89 lm/W Energieeffizienzklasse: A+ Betriebsspannung: 220 – 240 VAC, 50/60 Hz (Festanschluss) Farbtemperatur: 4.000 – 4.500 K Farbwiedergabeindex Ra: >80 Lichtstrom: 4.450 lm Abstrahlwinkel: 120° Abmessungen: 1.197 x 297 x 50 mm (L x B x H)	Service life: 40,000 h acc. IED/PAS 62717 Protection class: II protective insulation Protection category: IP20 Rated power: 50 W Luminous efficiency: 89 lm/W Energy efficiency class: A+ Operating voltage: 220 – 240 VAC, 50/60 Hz (fixed connection) Color temperature: 4,000 – 4,500 K Color rendering index: Ra > 80 Luminous flux: 4,450 lm Beam angle: 120° Dimensions: 1,197 x 297 x 50 mm (L x W x H)
Normen: <i>Standards:</i>	CE, RoHS, ENEC	

Lieferumfang

Scope of delivery

1x	LED Panel inkl. Treiber	<i>LED panel incl. driver</i>
1x	Aluminium T-Profil	<i>Aluminum T-profile</i>
2x	Vorreiber	<i>Sash lock</i>
1x	Dichtmaterial	<i>Sealing material</i>
1x	Montagematerial	<i>Mounting material</i>

Artikelnummer

Item number

Gangbreite [mm]	
<i>Aisle width</i>	
1200	506342100
1800	506342180