



Housing Material	Aluminium
Housing Color	White
Material of Lens	PMMA
Halogen free	Yes
Functions	Leuchte kann mit Gleichstrom aus einer Zentralbatterie eines Notstromsystems betrieben werden., Phase switch
Protection Class	Protection class I/protective grounding
Power Selectable	70 W, 64 W, 55 W, 49 W, 39 W, 34 W, 26 W, 20 W
Rated Input Voltage	198-264 V/AC
Dimmable	No
Voltage range DC	168-275 V/DC
Voltage range emergency lighting EOFI	186-250 V/DC 100 %

Working Temperature	-25 to 50 °C
Storage Temperature	-25 to 85 °C
IP Protection Class	IP 40
IK Protection Class	IK04
Life Time L70 / B50	130000 h
Life Time L80 / B10	72000 h
Life Time L80 / B50	85000 h
Switching Cycles	50000
Power Consumption	70 kWh/1000h

Light Source	LED, Light source changeable TC
Lightcolor	Neutral white
Color Temperature	4000 K
Colour Consistency	3 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	12200 lm
Luminous Efficiency	165 lm/W
Rated Angle of Reflection	90 Degree
UGR	25

Light characteristics	Direct
Light direction	Below

Length	1528 mm
Width	656 mm
Height	310 mm
Product weight	1950 g

