

**Special features**

- Very high colour rendering
- Can be rotated and swivelled
- Dimmable

Housing Material	Die-cast aluminium
Housing Color	White
Material of Lens	Plastic
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	24 W
Rated Input Voltage	34-35 V/DC
Rated Current	700 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	2150 lm
Luminous Efficiency	89.6 lm/W
Rated Angle of Reflection	36 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	85 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	97 mm
Diameter	165 mm
Installation Depth	100 mm

Cut Out Diameter	155 mm
Product weight	1012 g
Working Temperature	-5 to 40 °C
Storage Temperature	-20 to 50 °C
IP Protection Class	IP 20
Life Time L70 / B50	20000 h
Switching Cycles	15000
Power Consumption	24 kWh/1000h
Energy Efficiency Class	G