



Special features

- Modern minimalist design
- Powerful and energy-saving
- Uniform illumination
- Adjustable brightness threshold and operating time
- Base L x W x H: 125 x 135 x 15 mm

Housing Material	Die-cast aluminium
Housing Color	Grey
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Rated Input	18 W
Rated Input Voltage Frequency	110-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	Infrared
Detection Distance	6-10 m
Angle of Detection	120 Degree

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 54

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1650 lm
Rated Angle of Reflection	110 Degree
Distribution Characteristic 120°	DLS

Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	18 kWh/1000h
Energy Efficiency Class	F

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	140 mm
Width	172 mm
Height	219 mm
Base length	125 mm
Base width	135 mm
Base height	15 mm