lightnet

Beam Me Up-T1

Table light - Direct/indirect light distribution



Illustrations may only be similar and serve as an orientation.

Beam Me Up-T1. LED. Design table lamp, with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Snow White.

Direct/indirect light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80.

Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Reflector: Satin Gold. Separate stepless dimming of the direct/indirect light chambers. DxH (luminaire head, round/Stand). D=450mm.

H=90/1200mm. Medium-power current. 9050lm. 74W. 7,4kg. Binning initial <= MacAdam 3. Table clamp matching luminaire`s outer surface colour. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.


Article code: MT1AWX-840M-D450-TG-A


lightnet

Beam Me Up-T1

Table light - Direct/indirect light distribution







Article code: MT1AWX-840M-D450-TG-A

Customer	/ Project:			
Note:				

Productname Beam Me Up-T1

LampLEDInstallation TypeTable lightSurface finishSnow White

Light characteristics Direct/indirect light distribution

Colour temperature 4000K Colour Rendering Index (CRI) CRI>80

Optical system Microprismatic screen
Reflector Colour Inside Reflector: Satin Gold

Reflector Colour Inside Reflector: Satin Gold
Control Separately stepless dimmable

Length L/Diameter D (mm) D=450mm
Height H (mm) H=90/1200mm
Current/Power Medium-Power
Luminous Flux 9050lm

Luminous Flux9050lmPower consumption74WBase-TypeTable clamp

Plug Schuko CEE 7/7 (E+F)

Degree of protection IP20

LED lifetime L85B10 (tq 25° C) = 50.000h

UGR UGR<=19
Photometric code 8 40 / 3 3 9

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 7,4kg

