lightnet

Basic-P5

Pendant luminaire - Direct/indirect light distribution





Article code: BP5OSL-840H-D600-P

Illustrations may only be similar and serve as an orientation.

Basic-P5. LED. Pendant luminaire. Luminaire body with 38mm visible overall height and minimalist edge of only 5mm. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct/indirect light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Dimmable DALI. DxH (round). D=600mm. H=38mm. Rod suspension with ceiling rose (Set). Pendant

length on request. Ceiling rose: Matching luminaire's surface colour. High-power current. 8140lm. 63W. 6,4kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

lightnet


Basic-P5

Pendant luminaire - Direct/indirect light distribution

Article code: BP5OSL-840H-D600-P







LED Lamp Installation Type Pendant luminaire

Surface finish Radiant Silver

Light characteristics Direct/indirect light distribution

Basic-P5

4000K Colour temperature Colour Rendering Index (CRI) CRI>80 Optical system Opal diffuser Control Dimmable (DALI) Length L/Diameter D (mm) D=600mm H=38mm Height H (mm) Current/Power High-Power Luminous Flux 8140lm 63W Power consumption

Suspension Rod susp. (Set)

Ceiling rose: Matching luminaire`s Ceiling rose colour

surface colour

Pendant length (mm) Pendant length on request

Degree of protection IP40

Certification Prüfzeichen: ENEC

LED lifetime L80B10 (tq 25° C) = 50.000h

Photometric code 8 40 / 3 3 9 Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 6,4kg







Productname















