



Housing Material	Aluminium profile
Housing Color	Silver
Housing Surface	Brushed
Material of Lens	Plastic
Surface Structure of Lens	Satined
Protection Class	Protection class I/protective grounding
Rated Input	6 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	20000 h
Switching Cycles	10000
Power Consumption	6 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	490 lm
Rated Angle of Reflection	45 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	90 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Width	132 mm
Height	119 mm
Diameter	52 mm
Base height	35 mm
Base diameter	155 mm