

Phase sequence indicator - test plug

| Product description | |
|---|--------------------------|
| BALS-Prd.-Nr | 2216 |
| EAN | 4024941022163 |
| Product category | Phase sequence indicator |
| Current | 32A |
| Number of poles | 4p |
| Poles | 3P+PE |
| Position of earth contact | 9 h |
| Voltage | 200 up to 250V |
| Frequency | 50 and 60Hz |
| Protection degree | IP44 |
| Indication three phases | yes |
| Motor rotation direction tester | FALSE |
| Contact less detection of the sense of rotation | yes |
| Height | 142mm |
| Width | 66mm |
| Depth | 66mm |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.225 kg / Piece |
| Packaging | Bag |

| Logistics data | |
|----------------|---------------|
| Content amount | 1 ST |
| EAN | 4024941022163 |
| Length | 66 mm |
| Width | 66 mm |
| Height | 142 mm |
| Weight | 0.226 kg |
| Volume | 618.552 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941834407 |
| Length | 245 mm |
| Width | 177 mm |
| Height | 185 mm |
| Weight | 2.383 kg |
| Volume | 7,140 ccm |