



<b>Housing Material</b>	Die-cast aluminium
<b>Housing Color</b>	White
<b>Housing Surface</b>	Matt
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	4 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	Yes
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Motion Detector</b>	No

**Power Consumption** 4 kWh/1000h

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	2700 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	90
<b>Rated Luminous Flux</b>	22 lm
<b>Luminous Efficiency</b>	5.5 lm/W
<b>Rated Angle of Reflection</b>	100 Degree
<b>Light Distribution</b>	Symmetric

<b>Height</b>	35 mm
<b>Diameter</b>	65 mm
<b>Installation Depth</b>	60 mm
<b>Cut Out Diameter</b>	50 mm
<b>Product weight</b>	230 g

<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-20 to 50 °C
<b>IP Protection Class</b>	IP 20

<b>Life Time L70 / B50</b>	20000 h
<b>Switching Cycles</b>	10000