



Product Features

Patchpanel for DIN-rail mounting, Cat.6/ClassE, shielded, 6 TE (1TE=18mm), light grey (similar RAL 7035)

- for DIN-rail mounting (6 TE, 108 mm)
- insulation class II
- protection class IP 20
- for DIN-rail mounting
- quick one step mounting of strain relief and shieldung connection
- perfect shieldung
- clearly labelled LSA-terminals - color code
- color code T568A and T568B according to TIA/EIA-568-B.2
- LSA-contacts for one wire 0,4-0,63 mm Ø, AWG 26-22, maximum number of connections > 50-times
- universal jack for 6- and 8-pole plugs (RJ11/12)
- suitable for PoE++ / PPOE according to IEEE 802.3bt
- UPOE-konform
- HDBaseT-konform
- UPOE-konform
- HDBaseT-konform
- DIN EN 60 603-7-41, 250 MHz
- according to the following standards:
- ISO/IEC 11 801, Cat.6/ClassE, geschirmt
- DIN EN 50173-1, Cat.6/ClassE, geschirmt
- DIN EN 60603-7, 250 MHz, geschirmt
- life > 2500 cycles

Features

General	
Design	jack
shielded	Yes
Classification	Class E
PoweroverEthernet	Yes
Protection class IP	20
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921661987
Mounting types	
DIN-Rail	Yes

Dimensions/Weights without packaging	
Length mm	95
Width mm	108
Height mm	56
Net weight piece kg	0,198
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,254
Packaging unit Width mm	100
Packaging unit Height mm	116
Packaging unit Depth mm	76
References	
Accessories	23510201, 23510202, 23510503, 39200000
Similar article	13910200, 23510300

