



Housing Material	Aluminium	Installation Depth	40 mm
Housing Color	Silver	Cut Out Diameter	68 mm
Housing Surface	Brushed	Product weight	106 g
Protection Class	Protection class III/safety extra-low voltage	Working Temperature	-5 to 40 °C
Operating Mode	Constant current	Storage Temperature	-10 to 60 °C
Rated Input	5 W	IP Protection Class	IP 20
Rated Input Voltage	14-15 V/DC	Life Time L70 / B50	30000 h
Rated Current	350 mA	Switching Cycles	100000
Power Supply Unit incl.	No	Power Consumption	5 kWh/1000h
Connection Cable Secondary	Yes	Energy Efficiency Class	G
Secondary Connection	Open cables		
Secondary Cable Length	0.3 m		
Dimmable	Yes		
Control technology	Dimmable via optional power supply unit		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	2700 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	490 lm		
Luminous Efficiency	98 lm/W		
Rated Angle of Reflection	45 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Swivel Angle	25 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	30 mm		
Diameter	78 mm		