



Special features

- Particularly impact-resistant
- Feed-through wiring possible
- Light direction infinitely adjustable
- IP68-certified

Housing Material	Plastic
Housing Color	White
Housing Surface	Matt
Protection Class	Protection class I/protective grounding
Rated Input	40 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Motion Detector	No

Life Time L70 / B50	50000 h
Switching Cycles	25000
Power Consumption	40 kWh/1000h
Energy Efficiency Class	E

Light Source	LED, Light source not changeable
Color Temperature	5000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	4575 lm
Rated Angle of Reflection	100 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	NDLS

Swivel Angle	360 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	1300 mm
Diameter	39 mm

Working Temperature	-20 to 40 °C
Storage Temperature	-40 to 70 °C
IP Protection Class	IP 68/max. 2 m
IK Protection Class	IK10

