



LUCEA series pendant lamps are available in 10, 15 and 20 W versions and offer up to 2,000 lumens light output. The maximum suspended mounting is 1,800 mm. Using optional lenses, the light emission angle of the individual models can be narrowed or expanded. Lucea lights feature a die-cast aluminium housing

Special features

- High colour rendering
- Light colour adjustable in 2 stages
- Housing made from die-cast aluminium
- Max. suspended mounting 1,800 mm
- Dimmable

Housing Material	Die-cast aluminium
Housing Color	White
Material of Lens	PMMA
Protection Class	Protection class I/protective grounding
Rated Input	10 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	10 kWh/1000h
Energy Efficiency Class	F

Light Source	LED, Light source not changeable
Color Temperature	3000/4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	930/1000 lm
Rated Luminous Flux 2	1000 lm
Rated Angle of Reflection	36 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	157 mm
Diameter	65 mm
Pendulum Length max.	1800 mm

Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 65 °C
IP Protection Class	IP 20