

Han 24B-HTE2-HC-M32/M20-CL



Image is for illustration purposes only. Please refer to product description.

Part number	19 30 024 0483
Specification	Han 24B-HTE2-HC-M32/M20-CL
HARTING eCatalogue	https://b2b.harting.com/19300240483

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] B
Type of hood/housing	Hood
Type	High construction

Version

Size	24 B
Version	Top entry
Cable entry	1x M20 1x M32
Locking type	Central locking lever (on the hood)
Field of application	Standard hoods/housings for industrial connectors

Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)



Pushing Performance
Since 1945

Material properties

Material (locking)	Stainless steel
--------------------	-----------------

Specifications and approvals

Approvals	DNV GL
CE	Yes

Commercial data

Packaging size	1
Net weight	424 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140165137
eCl@ss	27440202 Shell for industrial connectors
